

Programming POS Keyboard KB78M-S

Specification

Key Number		78 keys
Key Switch Mechanism		Membrane - type Key Switch with 12 million life cycle time
Total Travel Distance		4 + 0.5mm / 2 + 0.6mm
Key Force (Peak Load		60 + 20cN
Interface / Power		USB: +5VDC + 10% / < 100mA
		PS/2: +5VDC + 10% / < 100mA
Cable		USB cable stored on the back
Programmable Features		
Programmable Keys		All keys can be programmable
Mufti - Level Programming		support max 6 levels
Time Delay Support		Provide a variable time delay, 0.5 sec per interval
True Keyboard Function		Provide true keyboard wedge function, operated with or without the normal
Software Compatibility		Support USB programming in Window ME/ 9X/2K/ XP/7/8/10
Memory		All programmed data are stored in EEPROM, without battery
Magnetic Stripe Card Reader Specification		
Card		Comply with ISO 7812, IBM standards, AAMVA, JIS - 2
Programmable Support		Programmable MSR setting for Header, Tailor, Separator, Suffix and Prefix
ISO Card Track	Track 1	210BPI with max 76 characters
	Track 2	210BPI with max 107 characters or 75BPI with max 37 characters
	Track 3	210BPI with max 107 characters
LEDs Indicator / Buzzer		Power, OK and ERROR
Swipe Speed / Head Life - Cycle		10 ~ 180 cm/sec. / 500, 000 swipes
Others		
Electronics Lock		6 section of electronic locks for different level users
Environment	Operating	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)
Physical	Storage	- 20°C ~ 55°C (-4°F ~ 131°F) , 10% ~ 90% (no condensation)
	Dim. / Weight	280 (L) x 175(D) x 52 (H) mm, including MSR/ 1038g(NW)
	Box / Weight	385 (L) x 196 (D) x 57 (H) mm / 1361g (GW)

Accessories

RJ45 Y Cable with PS/2 & USB interface, Key cap Puller,
1x and 2x Transparent Caps, Electronic keys

Picture

