

| SW-110N1 Technical         |      |
|----------------------------|------|
| Compatible with            |      |
| Channel                    |      |
| PMPO output                |      |
| Source input               |      |
| Device supports            |      |
| Bluetooth Version          |      |
| Bluetooth Range            |      |
| Frequency response:        |      |
| S/N ratio:                 |      |
| Distortion (THD):          |      |
| Output Power:              | SW:  |
|                            | BAR: |
| Separation:                |      |
| Input sensitive:           |      |
| Hum-noise output:          |      |
| Satellite impedance:       |      |
| Subwoofer impedance:       |      |
| Speaker(Driver) size:      | BAR: |
|                            | SW:  |
| Dimension:                 | BAR: |
|                            | SW:  |
| Power consumption (St.By): |      |
| Power consumption:         |      |
| Power supply:              |      |
| Remote control             |      |
| Remote control Battery     |      |
| Remote control range:      |      |
| Remote control angle       |      |
| Accessories                |      |

| Specification(FT3129*2+SMPS)                             |
|----------------------------------------------------------|
| TV, DVD, PC, Laptop, Tablet, Mobile, MP3, player etc..., |
| 2.1                                                      |
| /                                                        |
| USB/SD/BT/AUX/OPTICAL/HDMI(ARC)                          |
| USB/SD/MMC                                               |
| Dual mode bluetooth V5.0                                 |
| 10M(Without Barrier)                                     |
| 35Hz - 20KHz                                             |
| ≥68dB                                                    |
| ≤0.3% (1W 1KHz)                                          |
| 70W X 1                                                  |
| 20W X 2                                                  |
| ≥ 45db                                                   |
| 600mV                                                    |
| ≤ 3.0 mV                                                 |
| 4Ω                                                       |
| 4Ω                                                       |
| 2" X 2                                                   |
| 6.5" X 1                                                 |
| W800*D87*H87mm                                           |
| W250*D250*H415mm                                         |
| ≤3.5W                                                    |
| 70W+40W                                                  |
| AC100-240V 50/60Hz_ DC19V3.0A + DC24V4.0A                |
| Yes                                                      |
| /                                                        |
| 5m                                                       |
| 30°                                                      |
| User Manual, Warranty Card , Audio Cable, Remote control |