

Specification

Matrix Mainframe:

Model		S-Mix-E88	S-Mix-E1818	S-Mix-E3232	S-Mix-E7272
Interface	Input signals/Input cards	8/4	18/9	32/16	72/36
	Output signals/output cards	8/4	18/9	32/16	72/36
	Input modes	HDMI-4K-IN2, HSDA-IN2, 3GSDI-IN2, HDBaseT-IN2, FIBER-IN2			
	Output mode	HDMI-4K-OUT2, HSDA-OUT2, 3GSDI-OUT2, HDBaseT-OUT2, FIBER-OUT2			
	Bandwidth	10.2Gbps			
Control	RS232 control	Control protocol	RS232(Baud rate :115200, Data Bits:8, Stop Bits:1,no parity bit)		
		Connector	9 needles D-sub(DE9F) outlet 3=TX 2=RX 5=GND		
	TCP&IP control	Control protocol	TCP/IP		
		Connector	RJ45 joint 10/100Base-T Ethernet		
Size	Width	483mm	483mm	483mm	483mm
	Height	2.5U/110mm	6U/264mm	11U/484mm	25U/1100mm
	Depth	370mm	350mm	370mm	370mm
Electrostatic protection		Human-body discharge pattern: $\pm 8\text{kV}$ (Air-Gap Discharge) $\pm 4\text{kV}$ (Contact Discharge)			
Power		12 V/3 A DC (US/EU Standard, CE/FCC/UL Certified)			
Input voltage		Power100VAC~260VAC,50/60 Hz, International adaptive power 23W (Maximum)/0.5w(Standby)			
Operating Temperature		0°C~40°C			
Storage Temperature		-20°C~60°C			