



Category

SWITCH

SOCKET

WIRE HARNESS

BREAKER

FUSE HOLDER

FUSE

ENCODER

INDICATOR

POTENTIOMETER

CONNECTOR

WATERPROOF CONNECTOR

WATERPROOF PARTS

PCBA

NEW PRODUCT

Products Search

Search



OUR PRODUCT

Home » Our Product » AD60 SERIES INDICATORS » AD60 SERIES INDICATORS

INDICATOR / SCREW TYPE

AD60 SERIES INDICATORS
Pilot Lights, M16/22 mm, Various
Colors, Flashing or Bi-color, DC or AC
Voltage Indicators

Indicators for signal lamp purpose
Various colors, flashing of bi-color LED available
Wide selections of transparent PC cover heads,
including gear-shaped cover



PDF Download

Get Information

Print this page

Feature

FEATURES

- Continous working life: ≥30,000 hours
- Allow transient voltage fluctuation: ±20%(upon 110V)
- Withstand voltage: 2.5KV for 1min.
- Operating frequency: 50~60Hz
- Rated operational voltage: ≤20mA
- Light altitude: ≥100cd/m2
- Comparative tracking index: CT1≥100, antflaming
- Insulation resistance: Ui ≤ 60V for 5MΩ, 60≤ Ui ≤ 660V for 50MΩ
- Light: red, green, yellow, white, blue, flasing or Bi-color

Specification




How to order

AD60	16	D			G	12V
	INSTALL SIZE	PC COVER HEIGHT		BODY TYPE	LED COLOR	VOLTAGE AC/DC
	16 M16 mm 22 M22 mm	M16	M22	 Standard S Short body F Standard (flashing)	R Red G Green B Blue Y Yellow W White	6V 12V 24V 48V 110V 220V
		C 9.5mm flat D 3.5mm flat	A 13mm flat B 13.7mm flat C 11.5mm dome D 7mm flat E 7mm gear			





Item



AD60-16DSG



AD60-22DSR



BACK

