

Single-phase Bridge Rectifier 26MB060 thru 26MB120

Feature


- 6.3mm standard pin
- Low forward voltage drop
- Isolation voltage 2500V ~
- UL registered E304417

Application

- Power supply for DC power device
- Input rectifier for PWM convertor
- Power supply for DC device

Advantage

- Easy mounting
- Small volume, light weight
- Low thermal resistance
high heat-conduction rate
Low temperature rise



Maximum value

Symbol	Parameter	Rating				Unit
		26MB060	26MB080	26MB100	26MB120	
V_{RRM}	Peak reverse repetitive voltage	600	800	1000	1200	V
V_{RSM}	Peak reverse non-repetitive voltage	700	900	1100	1300	V




Symbol	Parameter	Test condition	Rating	Unit
$I_F (AV)$	Forward average current	180° sine half-wave 50HZ single-sided heat dissipation, $T_C=55^\circ C$	25	A
I_{FSM}	Forward surge current	$t=10ms, 50HZ, sin, T_{jm}$	300	A
I^2t	I^2t value		374	A ² S
V_{ISO}	Isolation voltage	AC one minute	2500	V
T_j	Operating junction temperature		-40 to +150	°C
T_{jm}	Rated junction temperature		150	°C
T_{stg}	Storage temperature		-40 to +125	°C
M_d	Mounting torque M5		2	N·m
W_t	Weight		18	g

Electrical characteristics

Symbol	Parameter	Test condition	Rating	Unit
I_{RRM}	Peak reverse repetitive current	$V_R=V_{RRM}$, sine half-wave, $T_j=25^\circ C$	5	μA
		$V_R=V_{RRM}$, sine half-wave, $T_j=150^\circ C$	500	μA
V_{FM}	Peak forward voltage	$I_{FM}=17.5A, T_j=25^\circ C$	1.1	V
$R_{th(j-c)}$	Thermal impedance (junction-case)	Single-sided heat dissipation, sine half-wave	1.9	°C/W

Single-phase Bridge Rectifier

26MB060 thru 26MB120



Single-phase Bridge Rectifier 26MB060 thru 26MB120



YANGZHOU POSITIONING TECH.CO.,LTD

Add:Room303 Weiheng Building No.184 Wangyue Rd,Yangzhou Jiangsu P.R.C 225009 ,China

Contact Person:John Chang, Sam Chou

Tel: +86-514-8778 2298,8778 2296 FAX:+86-514-8778 2297, 8736 7519

pst@globalsources.com, positioning@china.com

yzforever@163.net,pst@pst888.com

MSN ID: john_chang_370@hotmail.com

SKYPE ID : yzforever0313

Marketing web site:www.pst888.com, www.yzpst.net

<http://positioning.en.alibaba.com/>

<http://pst.manufacturer.globalsources.com/si/6008819407498/Homepage.htm>