

# Specifications

2.0MP,HD,Webcam

H.264,ONVIF,POE

IR night vision dome camera vandalproof

PC surveillance and mobile client

40m IR Distance



2014 New Products:Megapixel HD IR Night Vision Dome Security CCTV IP Camera,Web

| Model       | YC-W930AHBB89F           | YC-W931AHBB89F           | YC-W932AHBB89F                              |
|-------------|--------------------------|--------------------------|---------------------------------------------|
| CMOS sensor | 1/4" CMOS Sensor(OV9715) | 1/3"CMOS Sensor (AR0130) | 1/2.5" Progressive Scan CMOS Sensor (9P016) |
| Processor   | TI DM365                 | TI DM365                 | TI DM368                                    |

|                                |                                                                          |                |                 |
|--------------------------------|--------------------------------------------------------------------------|----------------|-----------------|
| Pixel                          | 1280(H)*720(V)                                                           | 1280(H)*720(V) | 1920(H)*1080(V) |
| Electronic shutter             | auto/ 1/60s-1/60000s                                                     |                |                 |
| Day/night mode                 | color/Black and white/auto/LDO control                                   |                |                 |
| Minimum Illumination           | Color: 0.05lux/F=1.2,Black and white:0.005lux/F=1.2                      |                |                 |
| Camera lens                    | Lens:3.6mm/6mm/8mm/2.8-12mm optional                                     |                |                 |
| Video coding                   | H.264 /JPEG coding                                                       |                |                 |
| Resolution                     | 1920x1080,1280X720,704X576,352X288                                       |                |                 |
| Dual stream                    | Main stream:1080P 720P,sub stream:D1 /CIF 25 frame per second(Real-time) |                |                 |
| Video compression              | 32Kbps-8Mbps Adjustable continuously,support fix/changeable bit rate     |                |                 |
| Audio                          | MIC input and active input,input and output volume adjustable            |                |                 |
| IR distance                    | 25-30m                                                                   |                |                 |
| Data storage style             | video recording storage, snapshot storage                                |                |                 |
| Storage means                  | manual, auto(timing, motion alarm)                                       |                |                 |
| Alarm data transmission        | FTP,Email,SD card,IE browser, client manager software(CMS)               |                |                 |
| Protocol                       | TCP/IP, UDP, DHCP, UPNP,DNS, IP filter,                                  |                |                 |
|                                | PPPOE, DDNS, FTP, Email, Alarm sever,ONVIF                               |                |                 |
| IE browser                     | Support IE,                                                              |                |                 |
| mobile phone viewing           | support iphone,blackberry,Andriod system                                 |                |                 |
| Interface                      |                                                                          |                |                 |
| Audio talkback input           | 1 channel input                                                          |                |                 |
| Audio output                   | 1 channel output                                                         |                |                 |
| storage interface              | support TF card(32 GB)                                                   |                |                 |
| Network interface              | RJ45 10M/100M network                                                    |                |                 |
| Reset                          | support                                                                  |                |                 |
| communication interface        | 1set RS485                                                               |                |                 |
| Environment                    |                                                                          |                |                 |
| Operating temperature/humidity | -10°C- +55°C /                                                           |                |                 |
| Waterproof level               | IP66                                                                     |                |                 |
| Input voltage/current          | 220mA/DC12V                                                              |                |                 |

**OEM Service:** We could offer OEM and ODM services for our clients.

**Delivery Time:** Sample order 3-5 working days, bulk order 7-15 working days.

**Quality Warranty:** 2 years for free repair. Whole life service for continue cooperating customers!

**Price Term:** FOB Shenzhen

**Delivery Term:** By Express(DHL/FEDEX/TNT/UPS/EMS/CHINA POST),By air,By Sea.

**FAQ:**

Q: How long is the warranty?

A: 2 -years-warranty since delivered out.

Q: What's the MOQ?

A: 1pc for sampe, at least 10pcs after sample order.

Q: How long is the delivery time?

A: Sample order 3-5 working days, bulk order 7-15 working days.

Q: Why do you choose us?

A: Choose YCX Co., Ltd; Choose a qualified CCTV Products manufacturer!

We will try our best to find the products you need, we will provide you with the most satisfactory service.  
If you want to learn more, You can contact me!



