

	A	B	C	D	E	F	G	H																																																																															
1									1																																																																														
2									2																																																																														
3									3																																																																														
4									4																																																																														
5									5																																																																														
6									6																																																																														
7	Features: 1 Electrical characteristics: A. Rated voltage: 150 volts AC. Rated current: 1.5 amps B. Voltage endurance test: less than 0.5 amperes at 1000 volts DC for one minute. C. Insulation resistance: 1000 volts DC/minute, greater than 500 million ohms D. Touch the pit: not more than 20mΩ (milliohms) 2 Mechanical characteristics: A. Tensile test - cable to socket tension strength of at least 20 pounds (89N) for at least one minute. B. Endurance test - pull-out test of more than 750 times. 3 Temperature range of use: -40 °C ~ + 85 °C 4 Environmental Compliance: A. The product complies with RoHS, REACH and other environmental specifications.								7																																																																														
8	<table><tr><td>☐ 屏蔽壳 Shell</td><td>☐ 黄铜 Brass</td><td>☐ 铁 Spcc</td><td>1</td></tr><tr><td>Au: ☐ G/F" ☐ 1u" ☐ 3u" ☐ Ni ☐ 80u"</td><td colspan="3"></td></tr><tr><td>胶壳 PC(聚碳酸酯) ☐ 94-V0 ☒ 94-V2</td><td colspan="3">1</td></tr><tr><td>金片 (PIN针) ☒ 黄铜 ☐ 磷铜 Contacts Brass Phosphor copper</td><td colspan="3"></td></tr><tr><td>☐ G/F" ☐ 1u" ☐ 3u" ☐ 6u" ☐ 15u" ☐ 30u" ☐ 50u" ☐ OTHER</td><td colspan="3">8</td></tr></table> <table><tr><td>BLADE:</td><td>平三叉</td><td>老三叉</td><td>拍扁三叉</td><td>高低三叉</td><td>高低矮三叉(专用)</td></tr><tr><td>Drawing</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>Mark</td><td></td><td></td><td></td><td></td><td></td></tr></table> <table><tr><td colspan="2">MM (INCH)</td><td>绘图 (Designed)</td><td colspan="2">XCCT 东莞市华翔电子有限公司 HUA XIANG Electronics Co.,Ltd</td></tr><tr><td colspan="2">公差 TOLERANCES</td><td>审核 (Checked)</td><td>系列 (SERIES)</td><td>名称 (NAME)</td></tr><tr><td>MM</td><td>MM</td><td>批准 (Approved)</td><td>RJ</td><td>六类头 双排通孔 1.2MM</td></tr><tr><td>.0 ± 0.20</td><td>.0 ± 0.38</td><td>材料 (Material)</td><td colspan="2">图号 (DWG NO.):</td></tr><tr><td>.00 ± 0.15</td><td>.00 ± 0.25</td><td>比例 (SCALE)</td><td colspan="2">料号 (PART NO.):</td></tr><tr><td>.000 ± 0.075</td><td>.000 ± 0.15</td><td>1:1</td><td>单位 (UNIT):</td><td>共 (SHEET) 1 页 第 (OF) 1 页</td></tr><tr><td colspan="2">角度 (ANGLES) ± 1.5°</td><td colspan="3"></td></tr><tr><td colspan="2"></td><td colspan="3">第三角视图</td></tr></table>								☐ 屏蔽壳 Shell	☐ 黄铜 Brass	☐ 铁 Spcc	1	Au: ☐ G/F" ☐ 1u" ☐ 3u" ☐ Ni ☐ 80u"				胶壳 PC(聚碳酸酯) ☐ 94-V0 ☒ 94-V2	1			金片 (PIN针) ☒ 黄铜 ☐ 磷铜 Contacts Brass Phosphor copper				☐ G/F" ☐ 1u" ☐ 3u" ☐ 6u" ☐ 15u" ☐ 30u" ☐ 50u" ☐ OTHER	8			BLADE:	平三叉	老三叉	拍扁三叉	高低三叉	高低矮三叉(专用)	Drawing						Mark						MM (INCH)		绘图 (Designed)	XCCT 东莞市华翔电子有限公司 HUA XIANG Electronics Co.,Ltd		公差 TOLERANCES		审核 (Checked)	系列 (SERIES)	名称 (NAME)	MM	MM	批准 (Approved)	RJ	六类头 双排通孔 1.2MM	.0 ± 0.20	.0 ± 0.38	材料 (Material)	图号 (DWG NO.):		.00 ± 0.15	.00 ± 0.25	比例 (SCALE)	料号 (PART NO.):		.000 ± 0.075	.000 ± 0.15	1:1	单位 (UNIT):	共 (SHEET) 1 页 第 (OF) 1 页	角度 (ANGLES) ± 1.5°							第三角视图			8
☐ 屏蔽壳 Shell	☐ 黄铜 Brass	☐ 铁 Spcc	1																																																																																				
Au: ☐ G/F" ☐ 1u" ☐ 3u" ☐ Ni ☐ 80u"																																																																																							
胶壳 PC(聚碳酸酯) ☐ 94-V0 ☒ 94-V2	1																																																																																						
金片 (PIN针) ☒ 黄铜 ☐ 磷铜 Contacts Brass Phosphor copper																																																																																							
☐ G/F" ☐ 1u" ☐ 3u" ☐ 6u" ☐ 15u" ☐ 30u" ☐ 50u" ☐ OTHER	8																																																																																						
BLADE:	平三叉	老三叉	拍扁三叉	高低三叉	高低矮三叉(专用)																																																																																		
Drawing																																																																																							
Mark																																																																																							
MM (INCH)		绘图 (Designed)	XCCT 东莞市华翔电子有限公司 HUA XIANG Electronics Co.,Ltd																																																																																				
公差 TOLERANCES		审核 (Checked)	系列 (SERIES)	名称 (NAME)																																																																																			
MM	MM	批准 (Approved)	RJ	六类头 双排通孔 1.2MM																																																																																			
.0 ± 0.20	.0 ± 0.38	材料 (Material)	图号 (DWG NO.):																																																																																				
.00 ± 0.15	.00 ± 0.25	比例 (SCALE)	料号 (PART NO.):																																																																																				
.000 ± 0.075	.000 ± 0.15	1:1	单位 (UNIT):	共 (SHEET) 1 页 第 (OF) 1 页																																																																																			
角度 (ANGLES) ± 1.5°																																																																																							
		第三角视图																																																																																					
	A	B	C	D	E	F	G	H																																																																															