

HSPOS TECHNOLOGY LIMITED
5 floor, A1 building, Nanshui Industrial Park, Sanjiao
Town, Zhongshan City, Guangdong Province, China
Tel +86 0760-85402097 Fax +86 0760-85402097
Website: www.hsprinter.com
Email: mikepeng@hsprinter.com



HS-KC31 3" thermal kiosk printer

Features:

- High Printing Speed up to 160mm/second;
- Support Windows2000/XP/7/8/10, Linux, Android
- Good price and Short delivery lead time
- Factory/Manufacture with engineer team, able to do OEM&ODM
- With cutter, mechanism, control board; With bracket optional
- SUPPORT USB+RS232/TTL Interface
- Support Logo download and print



Applications:

KIOSK & vending machine, queuing machine, Promotion coupon printing machine
Parking system, Gas station filling machine, Game machine & vote machine



HSPOS TECHNOLOGY LIMITED
 5 floor, A1 building, Nanshui Industrial Park, Sanjiao
 Town, Zhongshan City, Guangdong Province, China
Tel +86 0760-85402097 **Fax** +86 0760-85402097
 Website: www.hsprinter.com
 Email: mikepeng@hsprinter.com



Specifications:

Printing Method	Thermal
Dots/line	576dots/line
Resolution	203DPI
Printing Width(mm)	72mm
Paper Width(mm)	80mm
Paper diameter	MAX (150MM)
Feed Resolution(mm)	0.125
Interface	USB+RS232/usb+ttl
W x D x H(mm)	137.5x134.5x87.7mm(L*W*H)
Weight(kg)	0.35
Head temperature detection	Thermistor
Paper detection	Transmission photoelectricity switch
Black mark detection	Reflecting photoelectricity pipe
Platen position detection	Light touch swith
Operation voltage (V)	24V±10%
Graph Printing	Support different density Graph, raster bitmap and download bitmap
Language	Simplified Chinese, Traditional Chinese, English and other 45 kinds of international characters
Barcode	1D Bracode UPC-A, UPC-E, EAN-8, CODE39, ITF; CODE128, CODE93, QRCODE
Logical voltage(V)	5±0.25
Formfeeding motor voltage(V)	24±10%
Auto cutting motor voltage(V)	24±10%
Detection voltage (V)	5±0.25
Abrasion resistance	150 km
Auto cutting frequency	1 million times
Operating temperature(°C)	0 to 50 (no condensation)
Operating humidity(RH)	10% to 80% (no condensation)
Storage temperature(°C)	-25 to 70 (no condensation)
Storage humidity(RH)	5% to 95% (no condensation)